

Package: quiltr (via r-universe)

September 21, 2026

Title Qualtrics for Labelling Text using R

Version 0.1.0

Description Functions to convert text data for labelling into format appropriate for importing into Qualtrics. Supports multiple language, including right-to-left scripts as well as different response types. Outputs an Advance Format .txt file that can be read into Qualtrics.

License MIT + file LICENSE

URL <https://github.com/cjbarrie/quiltr>

BugReports <https://github.com/cjbarrie/quiltr/issues>

Language en-US

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.1.1

Suggests covr, knitr, rmarkdown, testthat (>= 3.0.0)

Config/testthat/edition 3

Depends R (>= 2.10)

VignetteBuilder knitr

Repository <https://cjbarrie.r-universe.dev>

Date/Publication 2021-12-03 08:36:23 UTC

RemoteUrl <https://github.com/cjbarrie/quiltr>

RemoteRef HEAD

RemoteSha 06d5578c217dbac6f1e09e41f5d56d6c2bec0e9d

Contents

arabiya_text	2
lipsum_text	2
qdat	3
quilt_form	3
quilt_form_data	4
Index	6

arabiya_text	<i>Arabiya politics text from SANAD dataset</i>
--------------	---

Description

A dataset containing one hundred paragraphs of politics labelled news from the SANAD Arabiya news data

Usage

arabiya_text

Format

A data frame with 100 rows and 1 variable:

text Paragraphs of Arabiya politics news ...

Source

<https://data.mendeley.com/datasets/57zpx667y9/2>

lipsum_text	<i>Lipsum text from stringi</i>
-------------	---------------------------------

Description

A dataset containing one hundred paragraphs of lipsum text

Usage

lipsum_text

Format

A data frame with 100 rows and 1 variable:

text Paragraphs of (pseudo) random lorem ipsum text ...

Source

https://www.rdocumentation.org/packages/stringi/versions/1.5.3/topics/stri_rand_lipsum

qdat	<i>Dataset generated with quilt_form_data</i>
------	---

Description

A dataset containing one hundred paragraphs of lipsum text with columns for text (prompt), response_type and ID

Usage

qdat

Format

A data frame with 100 rows and 3 variables:

prompt Paragraphs of (pseudo) random lorem ipsum text

response_type Response options separated with semi-colons

id Unique ID assigned to the text ...

Source

https://www.rdocumentation.org/packages/stringi/versions/1.5.3/topics/stri_rand_lipsum

quilt_form	<i>Create text labelling form for importing to Qualtrics</i>
------------	--

Description

Create text labelling form for importing to Qualtrics

Usage

```
quilt_form(input_data, page_break_every = 0, question_type, filename)
```


Arguments

prompt	character string: prompt of text for labelling, e.g.: "Label this text: "; defaults to NULL
text	character vector: text inputs for labelling
response_type	character vector: one of c("yesno", "options", "scale", "text")
options	character vector of response options: e.g., c("big", "small", "biggie smalls")
addID	add an ID variable to the text data
nlow	integer: low end of numeric scale
nhigh	integer: high end of numeric scale
remove_NA	if TRUE: removes empty rows of text

Value

a data.frame

Examples

```
## Not run:

data(lipsum_text)

qdat <- quilt_form_data(prompt = "Label this text: ",
                        text = lipsum_text$text, response_type = "yesno",
                        addID = T)

qdat <- quilt_form_data(prompt = "Label this text: ",
                        text = lipsum_text$text, response_type = "options",
                        options = c("Not at all", "Somewhat", "Very much"),
                        addID = T)

qdat <- quilt_form_data(prompt = "Label this text: ",
                        text = lipsum_text$text, response_type = "scale",
                        nlow = 1, nhigh = 10, addID = T)

## End(Not run)
```

Index

* **datasets**

arabiya_text, [2](#)

lipsum_text, [2](#)

qdat, [3](#)

arabiya_text, [2](#)

lipsum_text, [2](#)

qdat, [3](#)

quilt_form, [3](#)

quilt_form_data, [4](#)